

## **Agape Drill Site Permit Stipulations**

1. A sign will be displayed at the gate stating the well number, the name and number of the operator, the emergency 911 number, and the telephone numbers of two contacts.
2. The ambient sound level is established at 65.1 dBA. During drilling, the allowable nighttime sound level is 68.1 dBA and the allowable daytime sound level is 70.1 dBA. Fracing operations shall not exceed 72.1 dBA.
3. The approved water site plan allows a maximum flow rate of 800 gallons per minute.
4. The transportation route commences at State Highway (SH) 360. From SH 360, travel west on East Mayfield Road approximately 0.52 miles to Sherry Street. Head south on Sherry Street to site's access road on the east side of Sherry Street. Reverse the directions to exit from the site.
5. Landscaping shall be provided along all four sides on the outside of the masonry wall in accordance with the submitted site plan, Exhibit D-4, and shall be selected from the Texas Smartscape plant list. Shrubs, as identified on the plan, shall be planted at no more than three feet on center and canopy trees will be planted on center at no more than half of the specific species potential spread. The landscaping shall consist of Eastern Red Cedar and Live Oak trees and bare areas will be seeded with Bermuda grass.
6. Site development, other than drilling, shall be conducted from 6:00 a.m. to 7:00 p.m.
7. A secured entrance gate containing a Knox-Box keybox, pad lock, or equivalent is required. All gates must be kept locked when the Operator or his employees are not within the enclosure. Barbed wire fencing is not permitted below a point six feet above the surrounding grade. The well heads and site equipment shall be surrounded by a six-foot chain link fence having a gate and lock. Secure fencing is required at all times the Operator is not on-site once drilling operations commence.