

CH Enterprise Drill Site Permit Stipulations

1. A sign will be displayed at the gate stating the well number, the name and number of the operator, the emergency 911 number, and the telephone numbers of two contacts.
2. The ambient sound level is established at 59.6 dBA. During drilling, the allowable nighttime sound level is 62.6 dBA and the allowable daytime sound level is 64.6 dBA. Fracing operations shall not exceed a 66.6 dBA noise level.
3. The approved water site plan limits the rate of withdrawal to a maximum of 800 gallons per minute.
4. The transportation route commences at Interstate 820. From Interstate 820, take Division Street east approximately 5.06 miles to the site entrance driveway north of West Division Street. Reverse the directions to exit from the site.
5. Prior to drilling, trees must be planted along West Division Street and Oakwood Lane.
6. After completion of all wells, a solid masonry wall with a minimum height of eight feet must enclose all completed wells and tanks located within the operation site. A minimum of one gate, twelve feet wide, must be installed.
7. Additional trees shall be planted within a 20-foot transitional buffer on the north and west sides of the pad site.
8. Site development, other than drilling, shall be conducted only between the hours of 6:00 a.m. and 7:00 p.m.
9. A secured entrance gate containing a Knox-Box keybox or pad lock or equivalent is required. All gates are to be kept locked when the Operator or his employees are not within the enclosure. Barbed wire fencing is not permitted below a point six feet above the surrounding grade. The well heads and site equipment shall be surrounded by a six-foot chain link fence having a gate and lock. This required fence can either surround the entire site or be placed around the individual equipment areas. Secure fencing is required at all times the Operator or his employees are not on-site once drilling operations commence.