

GM Drill Site Permit Stipulations

1. A sign will be displayed at the gate stating the well number, the name and number of the operator, the emergency 911 number, and the telephone numbers of two contacts.
2. On-site noise monitors recorded the ambient noise level and established the 24-hour average sound level at 59.1 dBA. During drilling, the allowable nighttime sound level is 62.1 dBA and the allowable daytime sound level is 64.1 dBA. Fracing operations shall not exceed a 66.1 dBA noise level.
3. The approved water site plan limits the rate of withdrawal to a maximum of 800 gallons per minute.
4. The transportation route to the GM Drill Site commences at the intersection of State Highway (SH) 360 and East Abram Street. From this intersection, travel west approximately 0.72 miles north to GM Gate 11. Follow the access road to the GM plant and the drill site access road will be on the left immediately before the check-in gate. Reverse the direction to exit the site.
5. After completion of all wells, a solid masonry wall will enclose all completed wells and tanks located within the operation site.
6. Site development, other than drilling, shall be conducted only between the hours of 6:00 a.m. and 7:00 p.m.
7. A secured entrance gate containing a Knox-Box keybox or pad lock or equivalent is required. All gates are to be kept locked when the Operator or his employees are not within the enclosure. Barbed wire fencing is not permitted below a point six feet above the surrounding grade. The well heads and site equipment shall be surrounded by a six-foot chain link fence having a gate and lock. This required fence can either surround the entire site or be placed around the individual equipment areas. Secure fencing is required at all times the Operator or his employees are not on-site once drilling operations commence.