

## Royal Arch Drill Site Permit Stipulations

1. A sign will be displayed at the gate stating the well number, the name and number of the operator, the emergency 911 number, and the telephone numbers of two contacts.
2. The ambient noise level was established at 60.7 dBA. The allowable nighttime sound level is 63.7 dBA and the allowable daytime sound level is 65.7 dBA. Fracing operations shall not exceed 67.7 dBA.
3. Due to the proximity to protected uses, the exterior noise shall be continuously monitored by the operator in one-minute intervals and forwarded to the City daily.
4. The approved water site plan limits the rate of withdrawal to a maximum of 250 gallons per minute.
5. The transportation route commences at State Highway 360 (SH 360). From SH 360, take Division Street west approximately 3.5 miles to the site entrance driveway north of West Division Street. To exit from the site, travel west bound on Division Street past to the city boundary to the I-820.
6. Site development, other than drilling, shall be conducted only between the hours of 6:00 a.m. and 7:00 p.m., unless approval is obtained by the City.
7. A secured entrance gate containing a Knox-Box keybox or pad lock or equivalent is required. All gates are to be kept locked when the Operator or his employees are not within the enclosure. Barbed wire fencing is not permitted below a point six feet above the surrounding grade. The well heads and site equipment shall be surrounded by a six-foot chain link fence having a gate and lock. This required fence can either surround the entire site or be placed around the individual equipment areas. Secure fencing is required at all times the Operator or his employees are not on-site once drilling operations commence.